

according to 1907/2006/EC as amended by 453/2010/EC

6000- 4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 1 - 9

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ARTISTRI F700 CLEANING SOLUTION

Product code 6000- 4064

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

The product is only for industrial and/or professional use, not for any private consumer use.

1.3. Details of the supplier of the safety data sheet

Company/Undertaking Identification

Producer/Supplier DuPont Digital Printing
Street/Box Barley Mill Plaza
Nat.-Code/Postal code/City US Wilmington, DE

Product Information

Telephone +1 302 695 9682

Information on SDS

Responsible Department Regulatory Affairs
Telephone +49 (0)202 529-2385
Telefax +49 (0)202 529-2804

E-mail address sds-competence@deu.dupont.com

For further information, please also consult our Internet site

http://www.dupont.com

Section 2. Hazards identification

The mixture is non-dangerous in accordance with Directive 1999/45/EC.

2.1. Classification of the substance or mixture

Classification of the mixture

Not applicable.

2.2. Label elements

S-phrase(s)

S23 Do not breathe vapour.

S38 In case of insufficient ventilation, wear suitable respiratory equipment.

Section 3. Composition/information on ingredients

3.1. Substances

This product is a mixture. Health hazard information is based on its components.

3.2. Mixtures

Chemical characterization

Mixture of synthetic resins, pigments, and solvents

Hazardous components

Substances presenting a health or environmental hazard within the meaning of the DSD 67/548/EEC and/or (EC) 1272/ 2008 title II and annex VI as amended by (EC) 790/2009



EC

SAFETY DATA SHEET

according to 1907/2006/EC as amended by 453/2010/EC

6000- 4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 2 - 9

5.00 - < 7.00 %

CAS 107-21-1

EC 203-473-3 REACh no registration number available

Classification Xn: R22

[VI*] Acute Tox. 4, H302;

ethanediol

CAS 27306-78-1 Polyalkyleneoxide modified heptamethyltrisiloxane

REACh no registration number available 0.10 - < 0.20 %

Classification Xn: R20; Xi: R36; Xn: R48/20; N: R51/53

Eye Irrit. 2, H319; Acute Tox. 4, H332; STOT RE 2, H373; STOT RE 2, H373;

Aquatic Chronic 2, H411;

Up to the given revision date of this safety data sheet no REACh registration numbers are assigned to the chemical substances used in this preparation.

Additional advice

See full text of R-phrases in chapter 16. See full text of H-phrases in chapter 16.

[VI*]: Harmonised classification given by Annex VI of Regulation (EC) No 1272/2008 in its latest amended form

Section 4. First aid measures

4.1. Description of first aid measures

General advice

When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.

Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

4.2. Most important symptoms and effects, both acute and delayed

Please see practical experience in section 11.

4.3. Indication of any immediate medical attention and special treatment needed

If unconscious place in recovery position and seek medical advice.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray, Dry chemical, Foam.

Extinguishing media which shall not be used for safety reasons

High volume water jet



according to 1907/2006/EC as amended by 453/2010/EC

6000- 4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 3 - 9

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke containing hazardous combustion products. Exposure to decomposition products may be a hazard to health.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

5.3. Advice for firefighters

Fire and Explosion Hazards

The product is not flammable. Avoid heating above flash point.

Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep in a well-ventilated place. Keep away from sources of ignition. Do not inhale vapours.

6.2. Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems. Please avoid any emission of volatile organic compounds as possible.

6.3. Methods and materials for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

6.4. Reference to other sections

Comply with safety directives (see chapters 7 and 8).

Section 7. Handling and storage

7.1. Precautions for safe handling

Safe handling advice

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Comply with the health and safety at work laws. If material is a coating, do not sand, flame cut, braze or weld dry coating without an appropriate respirator or appropriate ventilation, and gloves.

Advice on protection against fire and explosion

Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Observe label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.



according to 1907/2006/EC as amended by 453/2010/EC

6000- 4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 4 - 9

Do not store together with explosives, compressed, liquefied and pressurised gases, aerosols, flammable liquids, oxidizing products, non combustible toxic products and infectious products.

Section 8. Exposure controls/personal protection

8.1. Control parameters

DNEL

CAS-No.	Chemical Name	End Use	Exposure routes	Fre- quency of exposure	Туре	Value
107-21-1	ethanediol	Workers	Dermal	Long term	Systemic effects	106 mg/kg
		Workers	Inhalative	Long term	Local effects	35 mg/m3

PNEC

CAS-No.	Chemical Name	Compartment	Туре	Value
107-21-1	ethanediol	Aquatic	Sediment	1.53 mg/kg
		Aquatic	Fresh water	10 mg/l
		Aquatic	Sea-water	1 mg/l

Occupational exposure limits

CAS-No.	Chemical Name		Time	Type	Value	Note
		Source				
107-21-1	ethanediol		15 min	IOELV15	104 mg/cm3	Skin
			15 min	IOELV15	40 ppm	Skin
			8 hr	IOELV8	52 mg/cm3	Skin
			8 hr	IOELV8	20 ppm	Skin

8.2. Exposure controls

Additional technical information on the plant

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn. Mask with gas filter, type A (EN 141)

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Glove material	Glove thickness	Break through time
Nitrile rubber	0.33 mm	60 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as



according to 1907/2006/EC as amended by 453/2010/EC

6000-4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 5 - 9

these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

Eye protection

Wear protective eyewear for protection against solvent spatter.

Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

Environmental exposure controls

Do not let product enter drains. For ecological information refer to section 12.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Form: liquid Colour: clear Odour: Odour is not perceptible.

Important health, safety and environmental information

Property	Value	Method
рН	No data available.	
Melting point/freezing point	Not applicable.	
Boiling point/boiling range	100 °C	
Flash point	100 °C	ISO 3679
		Does not sustain combustion.
Evaporation rate	Slower than Ether	
Flammability (solid, gas)	not relevant as product is liquid	
Lower explosion limit	no data available	
Upper explosion limit	no data available	
Vapour pressure	0.0 hPa	
Vapour density	no data available	
Relative density	$1 g/cm^3$	20 °C - DIN 53217/ISO 2811
Solubility(ies)		
Water solubility	completely miscible	
Solubility in other solvents	miscible with most organic solvents Listed in: Section	
	3. Composition/information on ingredients	
Partition coefficient:	This product is a mixture. For ingredient details see	
n-octanol/water	section 12	
Autoignition temperature	201 °C	DIN 51794 based on organic solvent
		content
Decomposition temperature	This product is a mixture. For further information see	
	section 10.	
Viscosity (23 °C)	20 s	ISO 2431 - 1993 6 mm
Explosive properties	Not explosive	
Oxidizing properties	not oxidizing	
	•	
9.2. Other data		

Solvent separation test	< 3%	ADR/RID
Content of volatile components	99.6 %	Basis Vapour pressure >= 0.01 kPa
(including water)		
organic solvent content	10.0 %	Basis Vapour pressure >= 0.01 kPa

Section 10. Stability and reactivity



according to 1907/2006/EC as amended by 453/2010/EC

6000- 4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 6 - 9

10.1. Reactivity

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.2. Chemical stability

The product is chemically stable.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials to avoid

not required under normal use

10.6. Hazardous decomposition products

None known.

Section 11. Toxicological information

11.1. Information on toxicological effects

General observations

There is no data available on the product. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

Practical experience

Swallowing may cause nausea, diarrhoea and vomiting.

Acute toxicity

Acute inhalation toxicity

EINECS-No.	Chemical Name	Species	Туре	Expo- sure time	Value	Method
	Polyalkyleneoxide modified heptamethyltrisiloxane	rat	LC50	4 h	2 mg/l	
Acute oral to	xicity					
EINECS-No.	Chemical Name	Species	Туре	Expo- sure time	Value	Method

LD50

> 2,000 mg/kg

Section 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses. The data in this section is consistent with data from chemical safety reports available at the date of revision.

rat

12.1. Toxicity

203-473-3

Aquatic toxicity

Acute toxicity aquatic invertebrates

ethanediol



according to 1907/2006/EC as amended by 453/2010/EC

6000- 4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 7 - 9

EINECS-No.	Chemical Name			Species	Туре	Exposure time	Value	Method
	Polyalkyleneoxide tamethyltrisiloxane	modified	hep-	Daphnia	EC50	48 h	22.6 mg/l	

Acute and extended toxicity of fishes

EINECS-No.	Chemical Name			Species	Type	Exposure time	Value	Method
	Polyalkyleneoxide tamethyltrisiloxane	modified	hep-	Danio rerio (ze- bra fish)	LC50	96 h	2.75 mg/l	

Toxicity with aquatic plants

EINECS-No.	Chemical Name			Species	Type	Exposure time	Value	Method
	Polyalkyleneoxide tamethyltrisiloxane	modified	hep-	Scenedesmus pannonicus	LC50	96 h	5.5 mg/l	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

Based on available data no ingredient is classified for this hazard property (please see section 3).

12.6. Other adverse effects

The preparation was evaluated in accordance with the conventional method of the preparations directive 1999/45/EC, and it was not classified as dangerous for the environment, but it does contain environmentally dangerous materials. For details, see section 3

Adsorbed organic bound halogens (AOX)

Product does not contain organic linked halogens contributing to AOX.

Section 13. Disposal considerations

13.1. Waste treatment methods

Dispose of in accordance with local regulations.

Product

Recommendation:

A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

Waste	Key I	Number	Description

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned packaging

Recommendation:

Properly emptied containers are to be scrap processed or reconditioned. Improperly emptied containers are considered hazardous waste (waste key number 150110).



according to 1907/2006/EC as amended by 453/2010/EC

6000-4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 8 - 9

Section 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

ADR/RID:in accordance with nota 1 of chapter 2.2.3.1.1 IMDG:in accordance with chapter 2.3.1.3 ICAO/IATA:in accordance with chapter 3.3.1.3

14.1. **UN** number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packaging group

Not applicable.

14.5. Environmental hazards

ADR/RID; IMDG; ICAO/IATA: none

Marine pollutant

IMDG: no

14.6. Special precautions for user

please see section 6 - 8

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Deliveries shall only be made based on appropriate packaging and in compliance with traffic laws.

Section 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The mixture is non-dangerous in accordance with Directive 1999/45/EC.

15.2. Chemical Safety Assessment

No safety checks were carried out on the mixture.

Section 16. Other information

Full text of R phrases with no. appearing in section 3

R20	Harmful by inhalation.
R22	Harmful if swallowed.
R36	Irritating to eyes.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environ-

ment.



according to 1907/2006/EC as amended by 453/2010/EC

6000- 4064 v1.0 Revision Date: 2012-07-09 Print Date: 2012-07-09 en/EU Page 9 - 9

Full text of H phrases with no. appearing in section 3

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to the kidneys/ liver/ eyes/ brain/ respiratory system/ central nervous
	system through prolonged or repeated exposure in contact with skin.
H411	Toxic to aquatic life with long lasting effects.

Information taken from reference works and the literature.

Substance No.	CAS no: www.cas.org./EO/regsys.html EC no: http://ecb.jrc.it/esis/index.php?PGM=ein
Substances presenting a health or environmental hazard within the meaning of Directive 67/548/EEC.	http://ecb.jrc.it/existing-chemicals/ http://ecb.jrc.it/classification-labelling/ http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB http://www.cdc.gov/niosh/ipcs/icstart.html
Other directives, limitations and prohibitory regulations	Directive 76/769/EC Directive 98/24/EC Directive 90/394/EC Directive 793/93/EC Directive 1999/45/EC Directive 2006/8/EC EUR-LEX: http://europa.eu.int/eur-lex/lex
Exposure limit for the pure substance	http://osha.europa.eu/OSHA

Training advice

Directive 76/769/EC Directive 98/24/EC

Further information

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU regulations and/or directives. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

Report version

Version	Changes
1.0	

Revision Date: 2012-07-09